












Introducing Purcee Industrial Power & Controls' Armored Cables

Utilizes a protective layer of metal, made of steel or aluminium providing enhanced durability and resistance to mechanical damage, moisture, and environmental hazards.

Types of Electrical Cables

-  Armored SWA 4 Core 4MM²
-  Armored SWA BL/LN XLPE/PVC 4CX16MM²
-  Armored SWA 4 Core 25MM²
-  Armored SWA BL/LN XLPE/PVC 4CX35MM²
-  Armored SWA BL/LN XLPE/PVC 4CX50MM²
-  Armored SWA BL/LN XLPE/PVC 4CX70MM²
-  Armored SWA BL/LN XLPE/PVC 4CX95MM²
-  Armored SWA 4 Core 120MM²
-  Armored SWA WH/LN 3CX185MM² XLP/HF11KV
-  Squared WH STRIP 3C 240MM XLPE COPPER 6.3/11KV
-  Earth Squared 1C 120MM PVC



No of Cores	Size mm ²	Approx. outer Diameter (mm) ± 4mm	Approx. Cable Weight (Kg/Km) ± 5%	Min. Bending Radius (mm)	Cutting Length (MT) ±10%	Flange/Outer Width	SPECIFICATIONS							
							Max. Conductor DC Resistance at 20 °c (Ω/Km)	Conductor AC Resistance at Max. Operating Temp. and 50Hz (Ω/Km)	Conductor S.C.C for 1 Sec (KA)	Current Carrying Capacity			Min. Bedding thickness (mm)	Min. Sheathing thickness (mm)
										Laid in Ground	In duct	Free Air		
4x4	16.8	16.8	580	251	1000	1250/760	4.61	5.878	0.57	49	38	47	0.6	1.24
4x16	24	24	1417	360	1000	1450/1200	1.15	1.46	2.29	105	79	101	0.6	1.24
4x25	27,6	27,6	1922	415	1000	1650/1200	0.727	0.927	3.58	141	106	136	0.6	1.25
4x35	30.5	30.5	2416	460	1000	1650/1200	0.524	0.668	5.01	170	128	166	0.6	1.32
4x50	32	32	2867	480	1000	1850/1200	0.387	0.493	7.15	238	174	218	0.6	1.4
4x70	36.8	36.8	4003	552	1000	1950/1600	0.268	0.342	10.02	293	218	277	0.76	1.56
4x95	39.5	39.5	5080	593	1000	2350/1600	0.193	0.246	13.59	350	260	337	0.76	1.64
4x120	44.8	44.8	6805	672	500	1850/1200	0.153	0.195	17.17	397	301	393	0.92	1.8
3X185	68.8	68.8	10384	1375	500	2350	0.0991	0.128	26.455	381	N/A	423	1.16	2.62
3X240	63.8	63.8	9068	960	500	2250	0.0754	0.098	34.32	575	N/A	601	N/A	2.28
1X120	15.9	15.9	1144	240	2000	1400/1200	0.153	0.183	13.8	N/A	219	337	N/A	N/A



Patrick Kasenda
(CEO)
Tel: +243 824 243 705